

20' SUPER PREDATOR



Triple Center Axles are standard on the 20' Super Predator. Shown here with standard used aircraft tires.



Our updated hydraulic phasing level lift system is a superior improvement over the outdated mechanical lift system.



CUTTING WIDTH



* Gearbox ratings based on field performance.







THE 20' SUPER PREDATOR HAS A 255 HP **TRANSFER GEARBOX WITH 210 HP CENTER** AND WING GEARBOXES.

FRONT AND REAR CHAINS, DUAL WING WHEELS, HYDRAULIC LEVEL LIFT, AND USED **AIRCRAFT TIRES ARE STANDARD EQUIP-**MENT ON THE 20' SUPER PREDATOR.



less area for rust to begin. Deck rings are standard.

SPECIFICATIONS

Cutting Width 238"
Transport Width 105"
Overall Width 246"
Overall Length 204"
Cutting Height 2"-15"
Blade Overlap 5"
Wing Lift Hydraulics Standard
Wing Flex 90° Up/22° Down
Jackstand Standard
Hitch Swivel Clevis
Blade Carrier Pan Stump Jumpers
Horsepower Required (min) 80 hp

Outboard Gearbox or Center & Wings*	2	10 hn	
•			
Output Shaft Diameter. 2"			
Cut Capacity	3	"	
BLADE TIP SPEED:			
Main or Center	540	15,992 FPM	
	1000	16,052 FPM	
Wings	540	15,384 FPM	
	1000	15,484 FPM	
DRIVELINE SIZE:			
Main Cat. 5			
Constant			
Veloc			
	V	CIOC.	

Divider Box*..... 255 hp

Main Gearbox or