



DISC SIZE	5-1/2"	6-1/2'	7-1/2'	9-1/2'
CUTTING WIDTH	66"	78"	90"	114"
MAX CUTTING DEPTH	6"	6"	6"	6"
HITCH TYPE	CAT. 1	CAT. 1	CAT. 1	CAT. 1 & 2
TRACTOR HP	25-35	35-60	40-65	60-95
NUMBER OF DISC	16	20	24	24
DISC BLADE DIA.	18"	20"	20''	22"
ANGLING (DEGREES)	2.3, 11.3, 20, 27.8	2.3, 11.3, 20, 27.8	2.3, 11.3, 20, 27.8	0, 7, 14, 21
BLADE MATERIAL	Heat Treated High Carbon Steel			
FRAME TYPE	3" Square Tubing	3" Square Tubing	3" Square Tubing	3" Square Tubing
DISC SPACING	7.5"	7.5"	7.5"	9"
GANG TYPE	3" Square Tubing	3" Square Tubing	3" Square Tubing	3" Square Tubing
GANG AXLES	1" SQ High Carbon Steel	1" SQ High Carbon Steel	1" SQ High Carbon Steel	1-1/8"SQ High Carbon Steel
BEARING TYPE	Maintenance Free Sealed Bearings	Maintenance Free Sealed Bearings	Maintenance Free Sealed Bearings	Maintenance Free Sealed Bearings —
APPROX. WEIGHT	751 lbs	857 lbs	958 lbs	1,248 lbs

## **FEATURES:**

- Constructed of heavy 1/4"x3"x3" square tubing
- Heat treated carbon steel blades
- No maintenance sealed bearings
- 1" & 1 1/8" high carbon steel square axles
- New hot-dipped galvanized frame for longer life

